

QUOTATION NO 092014-DCF

This quotation list all of the equipment needed to properly refill Dry Chemical Fire Extinguishers.

This is a basic quotation; options are listed at the end of the quotation that will offer faster, easier and more accurate fire extinguisher filling.

| Part No. | Description | Price |
|-------------------------|--|------------|
| 550-200 | Dry Chemical Powder Filling / Recovery System <ul style="list-style-type: none"> • 150 Lb powder capacity • Allows filling and reclaiming of dry chemical powder • Coned lid accepts standard 50 Lb supply pail • Operates on 80 psi pf shop air • Polypropylene Hopper / Tub • Discharge fittings for USA extinguishers included • Shippable via UPS • Enamel painted tubular frame <i>(System required for each type of dry chemical, ie; ABC, BC, PK,)</i> | \$ 1200.00 |
| 230-189 | Utility Dial Scale <ul style="list-style-type: none"> • 100 Lb x 4 oz capacity • 10" Dial face • 14" x 14" platform • Tare weight adjustment • Size: 13 ½" L x 9 ½" W x 14" T | 295.00 |
| 69-002 | Nitrogen Regulator <ul style="list-style-type: none"> • 450 psi outlet pressure • CGA 580 inlet • ¼" NPT outlet | 180.00 |
| 140-085 | Calibrated Pressure Gauge for Nitrogen Regulator <ul style="list-style-type: none"> • As required by NFPA #10 • 0-600 psi • Attaches to N2 regulator outlet • Stainless steel case | 125.00 |
| 200-048 | 10' Long N₂ Outlet Hose | 33.50 |
| 220-135 | Quick Release Air Chuck for N₂ Hose | 7.95 |
| 100-400 | Set of 12 Recharge Adapters with Air Valve | 195.00 |
| 393-025 | 6 Year Maintenance / Hydro Labels Roll of 500 <ul style="list-style-type: none"> • Meet NFPA #10 specifications • Imprinted with up to 5 lines | 68.00 |

Sub Total: \$2104.45



Hydro-Test Products Inc.
 85 Hudson Road Stow, Massachusetts 01775 USA
 Tel: 800-225-9488 / 978-897-4647 Fax: 978-897-1942
www.hydro-test.com

| <i>Optional Equipment for Filling Dry Chemical Fire Extinguishers:</i> | | Price |
|--|--|--------------|
| 550-301 | Powder Dust Collection Bench <ul style="list-style-type: none"> • Assist in keeping residual airborne powder under control • Operates on 110V Electrical • Mounted on adjustable leveling feet • Dimensions: 39" L x 28"D x 39"T • Table height at 33" • Easily replaceable filters | \$1395.00 |
| 550-305 | Automatic Shutoff Filling Assembly <i>Includes:</i> <ul style="list-style-type: none"> • 60 Lb capacity digital scale • Push button control box for filling 5, 10, 20Lb extinguishers • Automatically shuts Super 70 off when proper weight is reached • Override button for other capacities | \$ 2600.00 |

Utilities Required to Operate Equipment:

- Dry Chemical Fire Extinguisher Agent
- Nitrogen Supply Cylinder
- 8 CFM @ 80 psi of pre regulated shop compressed air
- 115V-20amp electrical (if purchasing any of the options)

Terms: **Discount is available** with prepayment terms (please [contact](#) our sales office for details)

F.O.B: [Stow, Massachusetts, USA](#), all freight cost are the responsibility of the purchaser. We will be pleased to offer delivered pricing upon request.

Delivery: Typically ship in 3 weeks

Valid: For 60 days

Warranty: All Hydro-Test Products manufactured equipment is warranted for a period of 12 months under normal usage, commencing after receipt of order. For items not manufactured by Hydro-Test Products the original manufacturer's warranty shall be in effect. Consumable items such as O-rings, Seals, Valves, etc... are warranted for 30 days under normal usage. All warrantee work is provided F.O.B. Stow, Massachusetts, USA.

Packaging: Best commercial packaging is included in the pricing. If export crating or other specialized or unique packaging is required an additional charge may apply.

Thank you for the opportunity to offer this quotation. To see pictures on the above products, please click on the **part no's** and you will be redirected to those items.

You can download our complete [catalog at this link](#)

Best regards,

Jon Gorman

[Jon Gorman](#)

Hydro-Test Products Inc.



Hydro-Test Products Inc.
 85 Hudson Road Stow, Massachusetts 01775 USA
 Tel: 800-225-9488 / 978-897-4647 Fax: 978-897-1942
www.hydro-test.com